

Answer Key - IN: Instrumentation Engineering

| Q.No. | Session | Que.Type | Sec. Name | Key | Marks |
|-------|---------|----------|-----------|----------------|-------|
| 1 | 1 | MCQ | GA | C | 1 |
| 2 | 1 | MCQ | GA | A | 1 |
| 3 | 1 | MCQ | GA | C | 1 |
| 4 | 1 | MCQ | GA | B | 1 |
| 5 | 1 | MCQ | GA | D | 1 |
| 6 | 1 | MCQ | GA | D | 2 |
| 7 | 1 | MCQ | GA | D | 2 |
| 8 | 1 | MCQ | GA | D | 2 |
| 9 | 1 | MCQ | GA | A | 2 |
| 10 | 1 | MCQ | GA | C | 2 |
| 1 | 1 | MCQ | IN | A | 1 |
| 2 | 1 | MCQ | IN | B | 1 |
| 3 | 1 | MCQ | IN | B | 1 |
| 4 | 1 | MCQ | IN | C | 1 |
| 5 | 1 | MCQ | IN | C | 1 |
| 6 | 1 | MCQ | IN | A | 1 |
| 7 | 1 | MCQ | IN | A | 1 |
| 8 | 1 | MCQ | IN | B | 1 |
| 9 | 1 | MCQ | IN | B | 1 |
| 10 | 1 | MCQ | IN | B | 1 |
| 11 | 1 | MCQ | IN | A | 1 |
| 12 | 1 | MCQ | IN | A | 1 |
| 13 | 1 | MCQ | IN | D | 1 |
| 14 | 1 | MCQ | IN | D | 1 |
| 15 | 1 | MCQ | IN | B | 1 |
| 16 | 1 | NAT | IN | 0.09 to 0.09 | 1 |
| 17 | 1 | NAT | IN | 7 to 7 | 1 |
| 18 | 1 | NAT | IN | 1.7 to 1.8 | 1 |
| 19 | 1 | NAT | IN | 2 to 2 | 1 |
| 20 | 1 | NAT | IN | 0.78 to 0.79 | 1 |
| 21 | 1 | NAT | IN | -4 to -4 | 1 |
| 22 | 1 | NAT | IN | 25 to 25 | 1 |
| 23 | 1 | NAT | IN | 223.3 to 223.5 | 1 |
| 24 | 1 | NAT | IN | 5 to 5 | 1 |

| | | | | | |
|----|---|-----|----|--------------------------|---|
| 25 | 1 | NAT | IN | 2.5 to 2.5 OR 3.5 to 3.5 | 1 |
| 26 | 1 | MCQ | IN | D | 2 |
| 27 | 1 | MCQ | IN | A | 2 |
| 28 | 1 | MCQ | IN | D | 2 |
| 29 | 1 | MCQ | IN | A | 2 |
| 30 | 1 | MCQ | IN | A | 2 |
| 31 | 1 | NAT | IN | 0.5 to 0.5 | 2 |
| 32 | 1 | NAT | IN | 0.7 to 0.7 | 2 |
| 33 | 1 | NAT | IN | 1 to 1 | 2 |
| 34 | 1 | NAT | IN | 115 to 116 | 2 |
| 35 | 1 | NAT | IN | 0 to 0 | 2 |
| 36 | 1 | NAT | IN | 5.0 to 5.1 | 2 |
| 37 | 1 | NAT | IN | 4 to 4 | 2 |
| 38 | 1 | NAT | IN | 1 to 1 | 2 |
| 39 | 1 | NAT | IN | 0.45 to 0.55 | 2 |
| 40 | 1 | NAT | IN | 7 to 7 | 2 |
| 41 | 1 | NAT | IN | 3.5 to 4.5 | 2 |
| 42 | 1 | NAT | IN | 199 to 201 | 2 |
| 43 | 1 | NAT | IN | 999 to 1001 | 2 |
| 44 | 1 | NAT | IN | 3.4 to 3.6 | 2 |
| 45 | 1 | NAT | IN | 0.95 to 1.05 | 2 |
| 46 | 1 | NAT | IN | 27.5 to 28.5 | 2 |
| 47 | 1 | NAT | IN | 200 to 200 | 2 |
| 48 | 1 | NAT | IN | 0 to 0 | 2 |
| 49 | 1 | NAT | IN | 14.5 to 15.0 | 2 |
| 50 | 1 | NAT | IN | -0.13 to -0.11 | 2 |
| 51 | 1 | NAT | IN | 1.8 to 1.8 | 2 |
| 52 | 1 | NAT | IN | 0.95 to 1.05 | 2 |
| 53 | 1 | NAT | IN | 4.3 to 4.6 | 2 |
| 54 | 1 | NAT | IN | 10 to 10 | 2 |
| 55 | 1 | NAT | IN | 65.4 to 65.6 | 2 |